SUPRA 950

A breakthrough in silence and reliability. For your large trucks.





Specifications

SUPRA 950

T model

- HFC R404A refrigerant
- 1,1 litre Tri-Vortex diesel engine
- ◆ 05G 6-cylinder compressor
- Standby motor
- Remote plug
- Low-noise sound control kit
- Automatic hot gas heating and defrost system
- Manual defrost
- Directly accessible oil gauge
- Moisture indicator
- Two sight glasses to monitor refrigerant level
- Dry air, fuel and oil filters
- ◆ 70-amp 12V alternator
- Pre-installed accessory package (electric fuel pump, fuel lines, battery cables)
- EasyCOLD[®] Microprocessor control system: Automatic Start/Stop
- Visual displays for: cooling heating defrost auto-start - temperature
- Programmable defrost interval
- Battery voltage indicator
- Automatic diesel restart
- Cab command with: Automatic pre-trip unit check function - Backlit Cab command display and keys to set and program the microprocessor parameters Safety devices:
- Standby motor overload protection
- Standby motor short cycle protection
- High coolant temperature protection
- Low engine oil protection
- Low and high refrigerant pressure protection
- Receiver tank pressure relief valve
- Top grille to protect from snow and rain

X model **SILENT**

 Ultra-low noise system with an identification and elimination of noise at its source

S model


Version without low-noise sound control kit

SUPRA Nordic: Extra features (T, X and S models):

High-capacity electrical and hot water heating

Accessories

- Battery
- Battery box
- Fuel tank 90 or 200 1
- Supply air sensor to avoid top freezing
- Automatic phase reverser 400/3/50 Hz
- Oil drain extension
- Additional water drain
- Fuel heater
- Control panel & cable extension



Today SUPRA innovates once more with a new range of sleek and aerodynamic, environmentfriendly units that demonstrate unparallelled low levels of noise (up to 70% reduction with T model).

Designed, engineered and manufactured with precision, this new range brings you the benefits of the latest technological developments for:

- Extremely silent operation,
- for operating in noise-sensitive areas

Exceptional reliability, for superior efficiency and enhanced product protection

Improved service **accessibility**, that reduces maintenance time, increases security and saves costs

Greater ease of use, with EasyCOLD® microprocessor control

Unheard-of sound levels reduced up to 4 decibels with the ultra-low noise kit.

Designed for large trucks with box volumes up to 90 m^3 , the SUPRA 950 is the highest capacity truck group available in the market. Also available as SUPRA Nordic 950 for ultimate performance and reliability in extreme low ambient temperatures.





Microprocessor cab command:

- proven reliability
- easy to use
- servicing functions
- T and S model: 1995 x 940 x 684

Required opening (mm): 1245 x 350

Refrigeration capacity

Evaporator return air	Operation (watts)	
temperature	Road	Standby
0 °C	10770	10030
– 20 °C	6450	6 190

Ambient temperature at + 30 °C (per A.T.P. procedure)

Airflow 2770 m³/h (constant at high & low speed) Weight T model: 610 kg X model: 625 kg S model: 596 kg



CARRIER TRANSICOLD EUROPE S.A.S. 10, boulevard de l'Oise

F-95031 CERGY PONTOISE CEDEX Phone: +33 (0)1 34 43 48 00 - Fax: +33 (0)1 34 43 48 48 www.carrier-transicold-europe.com

Carrier Transicold Europe S.A.S. au capital de 16 090 700 euros R.C.S. Pontoise B 410 041 776 - Code APE 518M - VAT: FR52410041776 The information contained in this document is not contractually binding, and may not be reproduced without prior approval. Printed in France (05/03) 62-61052-21

500 CARRIER SERVICE STATIONS in EUROPE, RUSSIA, MIDDLE EAST and AFRICA.





- Dimensions (mm)
- X model: 1995 x 940 x 724

	Evaporator return
	temperature
	0 °C